

Utilizes gas filter correlation technology to measure ambient levels of Nitrous Oxide concentrations

## Thermo Scientific Model 46i Nitrous Oxide Analyzer



### Key Features

- Gas filter correlation technology
- Linearity through all ranges
- Dual and auto range modes
- Automatic pressure and temperature correction
- Long term zero and span stability

The Thermo Scientific Model 46i Nitrous Oxide Analyzer utilizes gas filter correlation technology to measure ambient levels of Nitrous Oxide (N<sub>2</sub>O) concentrations. N<sub>2</sub>O has been identified as a primary greenhouse gas with a greater potential for global warming effects than Carbon Dioxide (CO<sub>2</sub>). The Model 46i analyzer helps users to comply with global greenhouse gas regulations.

The Model 46i analyzer uses an exact calibration curve to accurately linearize the instrument output over any range up to a concentration of 50 ppm, and is available in both dual and auto range modes.

In addition, the Model 46i analyzer features automatic pressure and temperature correction that provides an increased resistance to shock and

vibration while delivering enhanced specificity and sensitivity.

This state-of-the-art gas analyzer offers features such as an Ethernet port as well as flash memory for increased data storage.

Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be on-site.

Easily programmable short-cut keys allow you to jump directly to frequently accessed functions, menus or screens. The larger interface screen can display up to five lines of measurement information while the primary screen remains visible.

## Product Specifications

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

### Thermo Scientific Model 46i Nitrous Oxide Analyzer

<b>Preset Ranges</b>	0-0.2, 0.05, 1, 2, 5, 10, 20, and 50 ppm 0-0.5, 0.1, 2, 10, 20, 50, and 100 mg/m <sup>3</sup>
<b>Custom Ranges</b>	-0.2 to 50 ppm 0 - 0.5 to 100mg/ m <sup>3</sup>
<b>Zero Noise</b>	0.01 ppm RMS (30 second averaging time)
<b>Minimum Detectable Limit</b>	0.02 ppm (30 second averaging time)
<b>Zero Drift</b>	< 0.05 ppm (24 hour)
<b>Span Drift</b>	± 1% full scale (24 hour)
<b>Response Time</b>	60 seconds (0-90% at 30 second averaging time)
<b>Linearity</b>	± 2% full scale
<b>Sample Flow Rate</b>	0.5-2.0 liters/ min.
<b>Rejection Ratio</b>	Negligible interference from H <sub>2</sub> O, CO <sub>2</sub> , CO
<b>Temperature Range</b>	Performance specifications based on operation within 20°-30°C range (per U.S. EPA guidelines). Instrument may be safely operated over the range of 0°-45°C.
<b>Power Requirements</b>	100 VAC, 50/60 Hz, 115 VAC, 50/60 Hz, 220-240 VAC, 50/60 Hz, 275 watts
<b>Dimensions</b>	16.75"(W) x 8.62"(H) x 23"(D)
<b>Weight</b>	49 lbs. (22.2 kg)
<b>Outputs</b>	Selectable voltage, RS232/RS485, TCP/IP, 10 status relays and power fail indication (standard) 0-20 or 4-20 mA isolated current output (optional)
<b>Inputs</b>	16 digital inputs (standard), 8 0-10 Vdc analog inputs (optional)

### Ordering Information

#### Model 46i Nitrous Oxide Analyzer

Choose from the following configurations/options to customize your own Model 46i analyzer

#### Voltage options:

A = 120 VAC 50/60 Hz (standard)  
B = 220 VAC 50/60 Hz  
D = 220 VAC 50/60 Hz (China)  
J = 100 VAC 50/60 Hz

#### Application:

M= Ambient (standard)

#### Internal zero / span and O<sub>2</sub>:

N = No zero / span valve (standard)  
Z = Internal zero / span valves

#### Filter Wheel Purge:

S = Standard plumbing  
P= Filter wheel purge setup

#### Optional I/O:

A = None (standard)  
C = I/O expansion board (4-20mA outputs- 6 channels, 0-10v inputs- 8 channels)

#### Mounting Hardware:

A = Bench mounting (standard)  
B = Ears & handles, EIA  
C = Ears & handles, Retrofit

Your Order Code: Model 46i \_\_\_\_\_

Lit\_46iAQI\_11/10

© 2010 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

Air Quality Instruments

27 Forge Parkway  
Franklin, MA 02038 USA

(866) 282-0430  
(508) 520-0430  
(508) 520-1460 fax

[www.thermoscientific.com/AQI](http://www.thermoscientific.com/AQI)

**Thermo**  
SCIENTIFIC